



Technical data

Transport dimension



Working dimensions



| Terra Select | | | T 60 |
|-----------------------------|----|----------------|--|
| Transport Dimensions | | | |
| Machine length | At | mm | 12.000 |
| Machine height | Et | mm | 4.000 |
| Machine width | Ct | mm | 2.550 |
| Working Dimensions | | | |
| Machine length | Aw | mm | 16.100 |
| Machine height | Ew | mm | 4.000 |
| Machine width | Cw | mm | 7.370 |
| Operating conditions | | | |
| Temperature range | | °C | -10 / +37 |
| Infeed hopper | | | |
| Conveyor belt quality | | | EP 900/3 |
| Feeding quantity | | m ³ | > 6 |
| Feeding side | | | both sides |
| Feeding height | | mm | 2.870 |
| Feeding width | B | mm | 4.000 |
| Feeding depth | | mm | 1.800 |
| Belt width | | mm | 1.200 |
| Cleaning brush | | | |
| Diameter | | mm | 700 |
| Adjustment | | | hydraulic |
| Position | | | at left hand side in direction of travelling |

| Screen trommel | | | |
|---------------------------------|----|----------------|--|
| Trommel length | | mm | 5.500 |
| Trommel diameter | | mm | 2.200 |
| Trommel surface | | m ² | 38 |
| Trommel surface net | | m ² | 33 |
| Trommel material thickness | | mm | 6-12 |
| Trommel perforation | | mm | up to 80 |
| Trommel perforation types | | | round, square, rectangular, rhombus |
| Trommel perforation arrangement | | | in line or offset |
| Trommel speed | | u/m | Max. 21 |
| Discharge conveyors | | | |
| Fine belt length | | mm | 8.060 |
| Fine belt width | | mm | 1.000 |
| Fine belt discharge height | Ew | mm | 3.700 |
| Fine belt discharge angle | a | ° | 30 |
| Coarse grain belt length | | mm | 5.900 |
| Coarse grain belt width | | mm | 1.200 |
| Coarse grain discharge height | D | mm | 3.800 |
| Coarse grain discharge angle | b | ° | 30 |
| Drive unit | | | |
| Diesel engine | | | CAT C 3.6 12 V |
| Power | | kW | 75 |
| Engine size / Cylinder | | l | 3,6 / 4 Cylinder |
| Emission standard | | | Tier 4f / EU-Stage V |
| Tank volume | | l | 300 |
| Tank cover | | | Outside, at right hand side in direction of traveling, lockable |
| Switchboard | | | |
| Special features | | | with complete electric control and motor monitoring Machine operation: at right hand side in direction of traveling Medium Sound pressure level LP A max = 89,1 dB (A) |
| Undercarriage | | | |
| | | | 2-axle trailer acc. to German Traffic Rules with ABS |
| Tyres | | | 385/65 R22,5 |
| Total admissible weight | | kg | 19.000 |
| Lighting system 24V | | V | 24 |
| Towing eye | | D (mm) | 50 |
| Painting | | | |
| Machine | | | Blue RAL 5010 |
| Layer thickness | | µm | >120 |
| Conveyor belt frame | | | lacquered |